

# CERTIFICATE ENEC/FI 2016081



Our Ref. 281658-1

**Product** Electronic control gear for LED module

**Rating and principal characteristics** See page 2

**Trade mark (if any)** Helvar

**Type** LC1x35 Active+, LC1x25 Active+

**Name and address of the licensee** Helvar Oy Ab  
Keilaranta 5  
FI-02150 ESPOO, FINLAND

**Address of the manufacturer** Helvar Oy Ab  
Keilaranta 5  
FI-02150 ESPOO, FINLAND

**Is in conformity with** EN 61347-2-13:2014  
EN 61347-1:2008 + A1:2011 + A2:2013  
EN 62384:2006 + A1:2009

**As shown in the Test Report(s) No(s)** 281658-3\_A, 281658-3\_B

**It is authorized to use of the marks** ENEC 16 and FI

**Validity** This certificate is valid until 22 December 2021 provided that the Conditions for ENEC and FI certification are met. This certificate includes the right to use the ENEC 16 and FI mark under the condition that product changes (if any) will be approved at SGS Fimko before the product is brought onto market.

**Directive information** The certified product(s) fulfils requirements of above mentioned standard(s) which are harmonised under the Low Voltage Directive (2014/35/EU) at the date of issue of the certificate.

**With the following limitations** -

**Date of issue** 22 December 2016

**SGS Fimko Ltd**

**Signature**

Peter Fagerstedt

Certification Manager



This certificate has 3 pages



This certificate is issued by the company under its General Conditions for Certification Services accessible at <http://www.sgs.fi/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this certificate. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**Rating and principal characteristics**

LC1x25 Active+:  
 220-240VAC; 0/50-60Hz; Constant current 350mA/9...48V or  
 700mA/9...36V; tc +75°C; λ0,91...0,95; P-OUTmax: 25,2W;  
 U-OUTmax: 60V; ta: -20...+50°C, SELV, EL marked

LC1x35 Active+:  
 220-240VAC; 0/50-60Hz; Constant current 700mA/9...48V or  
 1050mA/9...34V; tc +75°C; λ0,96; P-OUTmax: 35,7W;  
 U-OUTmax: 60V; ta: -20...+50°C; independent use: ta: -20...+40°C,  
 SELV, EL marked

**Additional information**



**Is based on test / Our ref.**

281658-3\_A  
 281658-3\_B

