

Presence detector - Professional Line

IR Quattro HD

DALI-2 Input Device
EAN 4007841 057497



infrared sensor
360°



max. 8m x 8m
presence

HD

4800 zones



ideal 2,5 - 10 m



indoor sensor



IP20



10 - 10000 lux



energy saving

5 JAHRE
HERSTELLER
GARANTIE

manufacturer's
warranty
[steinel-professional.de/garantie](https://www.steinel-professional.de/garantie)

CE

CE

Function description

Detection no finer! Infrared presence detector Presence Control PRO IR Quattro HD DALI-2 Input Device for indoors, ideal for medium to large-size offices, conference and meeting rooms, classrooms and lecture theatres, sports halls and warehouses, installation height up to 10 m. DALI-2 Input Device enables sensors to communicate collected sensor data to higher-level lighting management systems.

IR Quattro HD

DALI-2 Input Device
EAN 4007841 057497

Technical specifications

Type	Presence detector
Dimensions (L x W x H)	50 x 120 x 120 mm
Mains power supply	12 – 22,5 V
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	classroom, lecture hall, open-plan office, high-bay warehouse, production facilities, conference room / meeting room, duty room, recreation room, changing room, sports hall, reception / lobby, multi-storey / underground car park, Indoors
Installation site	ceiling
Installation	Concealed wiring
Switching zones	4800 switching zones
Electronic scalability	No
Mechanical scalability	Yes
Mounting height	2,50 – 10 m
Optimum mounting height	2,8 m
Detection angle	360 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Reach, radial	8 x 8 m (64 m ²)
Reach, tangential	20 x 20 m (400 m ²)

Reach, presence	8 x 8 m (64 m ²)
Twilight setting TEACH	Yes
Twilight setting	10 – 1000 lx
Switching output 2, floating	No
Control output, Dali	Addressable/slave
Basic light level function	No
Functions	Presence function
With bus coupling	Yes
Settings via	Bus
With remote control	No
Interconnection	Yes
Material	Plastic
Ambient temperature	-25 – 50 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	DALI-2 Input Device
PU1, EAN	4007841057497


Accessories

EAN 4007841 003036	Control PRO guard cage
EAN 4007841 000363	Surface-mounting adapter Control PRO AP Box (IP54)

IR Quattro HD


DALI-2 Input Device
EAN 4007841 057497

Detection Zone



Mögliche Montagehöhe: 2,50 m – 10,00 m
Orange: Präsenz
Schwarz: tangential

Dimension Drawing



Circuit diagram

